

BRO TN650 ISO19752 Yield Test Report

Declaration of Yield:

**Toner cartridge yield: Average Cartridge Yield 8000 standard pages.
Declared yield value in accordance with ISO/IEC 19752**

Average **8024**
Standard deviation **56**
90% Lower Confidence **7989**

Date Tested : 2012/05/29-2012/06/05

For question concerning testing contact: LTES

Number of Cartridges used in testing: 9
 Number of Cartridges used in calculations: 9
 Type of Cartridge Two-part
 Shake Procedure used? Yes, at standard page low density appears. The life is over when the printout appears to be fading after the Third shake.
 Print mode: Continuous(500 pages/job)
 Number of engines used in testing: 3
 Media Used: TIANZHANG copy paper 80g
 Paper size: A4
 Paper feed orientation: Short edge feed
 Computer Model: FUJITSU C601FMV
 Driver Version: Brother HL-5250
 Operating System: Windows XP
 Application Software: Adobe Reader 9.1
 Test Page Version: Version 2.1
 Power (off/on) everyday? Yes

Cartridge serial numbers(Cartridge type: TN650)

1#	4#	7#
2#	5#	8#
3#	6#	9#

Engine serial numbers(Engine Type: Brother HL-5250)

E70158F2J170485
 E70158F1J154589
 E70158E1J154739

Cartridge testing date:

Cartridge	Engine	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg	Max	Min	Avg	Max	Min		
1#	E70158F2J170485	23.1	24.5	21.8	52.4	54.6	50.2	8029	Y
2#		23.2	24.3	22.2	49.9	53.1	46.7	7951	Y
3#		22.4	23.8	21.1	51.8	53.4	50.1	8010	Y
4#	E70158F1J154589	22.7	23.8	21.6	51.5	53.9	49.0	8122	Y
5#		23.3	23.7	22.8	51.4	53.3	49.5	7958	Y
6#		22.4	23.6	21.2	51.0	53.3	48.7	8058	Y
7#	E70158E1J154739	22.7	24.4	21.0	51.9	54.6	49.2	8064	Y
8#		23.0	24.0	22.0	52.1	54.6	49.7	7976	Y
9#		22.3	23.0	21.7	50.0	54.1	45.9	8048	Y

Remark:

- 1) Hav'nt use the modify function of print quality.
- 2) The light printout don't count in the cartridge yield.