

TN450 ISO19752 Yield Test Report

Declaration of Yield:

Toner cartridge yield: Average Cartridge Yield 2600 standard pages.
Declared yield value in accordance with ISO/IEC 19752

Average **2640**
 Standard deviation **38**
 90% Lower Confidence **2616**

Date Tested : 2012/05/19-2012/05/25

For question concerning testing contact: LTES

Number of Cartridges used in testing: 9
 Number of Cartridges used in calculations: 9
 Type of Cartridge Two-part
 Shake Procedure used? Yes, at standard page low density appears. The life is over when the printout appears to be fading after the Third shake.

Print mode: Continuous(500 pages/job)
 Number of engines used in testing: 3
 Media Used: TIANZHANG copy paper 80g
 Paper size: A4
 Paper feed orientation: Short edge feed
 Computer Model: FUJITSU C601FMV
 Driver Version: Brother HL-2240
 Operating System: Windows XP
 Application Software: Adobe Reader 9.1
 Test Page Version: Version 2.1
 Power (off/on) everyday? Yes

Cartridge serial numbers(Cartridge type: TN450)

1#	4#	7#
2#	5#	8#
3#	6#	9#

Engine serial numbers(Engine Type: Brother HL-2240)

E69528G1J918878
 E69578B1J622776
 E69578A1J532212

Cartridge testing date:

Cartridge	Engine	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg	Max	Min	Avg	Max	Min		
1#	E69528G1J918878	23.2	24.3	22.2	51.3	53.4	49.1	2604	Y
2#		22.7	24.2	21.2	50.8	54.1	47.6	2600	Y
3#		23.0	24.5	21.6	51.8	53.7	49.8	2626	Y
4#	E69578B1J622776	22.4	23.5	21.3	50.1	54.5	45.8	2663	Y
5#		22.9	24.6	21.1	50.7	54.8	46.5	2637	Y
6#		22.9	23.5	22.2	49.2	53.1	45.2	2697	Y
7#	E69578A1J532212	23.6	24.5	22.7	51.4	54.0	48.9	2601	Y
8#		23.1	24.6	21.6	51.6	53.0	50.1	2698	Y
9#		22.5	23.2	21.9	51.0	53.8	48.2	2632	Y

Remark:

- 1) Hav'nt use the modify function of print quality.
- 2) The light printout don't count in the cartridge yield.