

ML-1610/2010/SCX-4521/3117 BK HY ISO19752 Yield Test Report

Declaration of Yield:

Toner cartridge yield: Average Cartridge Yield 3000 standard pages.
Declared yield value in accordance with ISO/IEC 19752

Average **3143**
 Standard deviation **81**
 90% Lower Confidence **3093**

Date Tested : 2012/06/12-2012/06/15

For question concerning testing contact: LTES

Number of Cartridges used in testing: 9
 Number of Cartridges used in calculations: 9
 Type of Cartridge All-in-one
 Shake Procedure used? Yes, at standard page low density appears. The life is over when the printout appears to be fading after the Third shake.

Print mode: Continuous(500 pages/job)
 Number of engines used in testing: 3
 Media Used: TIANZHANG copy paper 80g
 Paper size: A4
 Paper feed orientation: Short edge feed
 Computer Model: FUJITSU C601FMV
 Driver Version: Samsung ML-1610
 Operating System: Windows XP
 Application Software: Adobe Reader 9.1
 Test Page Version: Version 2.1
 Power (off/on) everyday? Yes

Cartridge serial numbers(Cartridge type: ML-1610)

| | | |
|----|----|----|
| 1# | 4# | 7# |
| 2# | 5# | 8# |
| 3# | 6# | 9# |

Engine serial numbers(Engine Type: Samsung ML-1610)

4F61BAGQB00204H
 4F61BKAQ317110N
 4F75BAG5700141F

Cartridge testing date:

| Cartridge | Engine | Temperature | | | Humidity | | | Cartridge Yield | Cart used in Calculation |
|-----------|-----------------|-------------|------|------|----------|------|------|-----------------|--------------------------|
| | | Avg | Max | Min | Avg | Max | Min | | |
| 1# | 4F61BAGQB00204H | 22.6 | 23.6 | 21.6 | 50.8 | 56.3 | 45.2 | 3174 | Y |
| 2# | | 23.2 | 25.8 | 20.6 | 49.2 | 52.8 | 45.6 | 3242 | Y |
| 3# | | 23.5 | 25.6 | 21.4 | 49.3 | 52.8 | 45.9 | 3121 | Y |
| 4# | 4F61BKAQ317110N | 22.1 | 23.0 | 21.3 | 50.4 | 54.2 | 46.5 | 3004 | Y |
| 5# | | 23.3 | 24.5 | 22.0 | 49.4 | 53.6 | 45.2 | 3122 | Y |
| 6# | | 23.4 | 24.0 | 22.8 | 50.5 | 54.8 | 46.2 | 3095 | Y |
| 7# | 4F75BAG5700141F | 23.3 | 25.5 | 21.2 | 52.4 | 55.8 | 49.1 | 3229 | Y |
| 8# | | 23.8 | 25.5 | 22.0 | 50.9 | 54.2 | 47.6 | 3225 | Y |
| 9# | | 22.9 | 24.1 | 21.6 | 49.6 | 52.8 | 46.5 | 3073 | Y |

Remark.

- 1)Hav'nt use the modify function of print quality.
- 2)The light printout don't count in the cartridge yield.

For and on behalf of
Prime Success Company Limited



.....
 Authorized Signature(s)