

SCX-4824/ML-2855 HY ISO19752 Yield Test Report

Declaration of Yield:

Toner cartridge yield: Average Cartridge Yield 5000 standard pages.
Declared yield value in accordance with ISO/IEC 19752

Average **5127**
 Standard deviation **54**
 90% Lower Confidence **5093**

Date Tested : 2012/05/22-2012/05/29

For question concerning testing contact: LTES

Number of Cartridges used in testing: 9
 Number of Cartridges used in calculations: 9
 Type of Cartridge All-in-one
 Shake Procedure used? Yes, at standard page low density appears. The life is over when the printout appears to be fading after the Third shake.
 Print mode: Continuous(500 pages/job)
 Number of engines used in testing: 3
 Media Used: TIANZHANG copy paper 80g
 Paper size: A4
 Paper feed orientation: Short edge feed
 Computer Model: FUJITSU C601FMV
 Driver Version: Samsung ML-2853
 Operating System: Windows XP
 Application Software: Adobe Reader 9.1
 Test Page Version: Version 2.1
 Power (off/on) everyday? Yes

Cartridge serial numbers(Cartridge type: SCX-4824/ML-2855 HY)

1#	4#	7#
2#	5#	8#
3#	6#	9#

Engine serial numbers(Engine Type: Samsung ML-2853)

BE54B1BL800018E
 BA51G0B1508D512
 BE51BD52592000F

Cartridge testing date:

Cartridge	Engine	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg	Max	Min	Avg	Max	Min		
1#	BE54B1BL800018E	22.5	23.1	22.0	51.4	53.4	49.3	5083	Y
2#		24.1	25.4	22.8	50.7	54.1	47.3	5182	Y
3#		22.3	23.4	21.1	50.8	54.5	47.2	5160	Y
4#	BA51G0B1508D512	22.5	24.1	20.8	51.2	52.9	49.6	5053	Y
5#		22.5	24.5	20.5	52.2	55.3	49.0	5169	Y
6#		22.0	23.8	20.2	53.6	56.5	50.6	5110	Y
7#	BE51BD52592000F	24.0	25.3	22.6	50.3	55.3	45.3	5061	Y
8#		22.3	24.2	20.5	51.3	53.2	49.4	5201	Y
9#		22.7	24.3	21.0	49.9	52.7	47.1	5120	Y

Remark:

- 1) Hav'nt use the modify function of print quality.
- 2) The light printout don't count in the cartridge yield.

For and on behalf of
Prime Success Company Limited



.....
 Authorized Signature(s)